Caravan Service Checklist

(from an Eriba Ltd service, October '03)

Exterior

Remove jockey wheel and grease	
3 X grease nipples on hitch	
Grease ratchet on handbrake	
Grease coupling	
5	
Check safety cable	
4 X Grease nipples on axle (where applicable)	
Remove wheels & check tyres	
(especially tyre walls)	
Remove wheel hubs	
Check expanding clutches (make	
sure correct model has been fitted)	
Check brake shoes and clean	
Depending on the model year,	
either:	
A. Re-pack bearing with grease	
& fit new split-pin	
B. Fit new one-shot nut	
Adjust brakes as per Al-Ko	
handbook	
Check tyre pressures, incl. spare	
wheel	
Torque wrench wheel studs	
Grease corner steadies	
Check underside of caravan	
Lubricate all locks & padlock, &	
Mains input socket	
Lubricate door hinges	
Depending on model year, either:	
A. Check 12N &12S plugs and lubricate	
B. Check Euro 13 plug and	
lubricate	
Remove rear lens units & clean	
Check road lights	
Clean off roof mechanism &	_
lubricate with Vaseline	
Check fibreglass roof	
Check canvas on elevating roof	
Check awning brackets	

Interior

Gas check	
Test all gas appliances	
Fit new gas hose	
Check 'fridge gets cold on gas &	
mains	
Check battery + levels + slow	
charge for 24 hrs. + condition test	
Check charge is coming to battery	
from 12S plug	
Check 12V supply to fridge	
Check 12V pump	
Check 12V & mains lights	
Check 12V sockets (where fitted)	
Check Thetford cassette toilet	
(where fitted)	
Check RCCB & polarity in mains	
sockets	
Check opening windows	
Check window bracket screws are	
tight	
Check cassette blinds (where	
fitted)	
Check table rail on table	
Lubricate cupboard catches (metal	
type only)	
Check operation of roof	
Lubricate roof securing fasteners	
Check for any water leak from sink	
waste	
Check furniture	

Road Test caravan

Advise of any faults found, not listed above	
Advise of any replacement parts used	
Wash caravan	
Re-check wheel studs	

Additional work to be carried out :Perform water ingress test re.
Extended warranty

To this list I would add: check operation of hitch coupling; check condition of friction pads in coupling (where fitted)

The invoice says: PLEASE NOTE! CHECK WHEEL STUDS AFTER 40 MILES.